# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000216

International filing date: 21 January 2005 (21.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB

Number: 0401500.4

Filing date: 23 January 2004 (23.01.2004)

Date of receipt at the International Bureau: 25 February 2005 (25.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)







PUT/GB2005/000216.

The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

INVESTOR IN PEOPLE

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

10 February 2005

Willia Morell

. .

ats Act 1977 **Office** (Rule 16) THE PATENT No Fee Request for grant of a patent The Patent Office (See the notes on the back of this form. You can also get **Cardiff Road** 23 JAN 2004 an explanatory leaflet from the Patent Office to help Newport you fill in this form) South Wales NP10 8QQ LONDON Your reference 1. RA/P302798GB 0401500.4 2. Patent application number 2 3 JAN 2004 (The Patent Office will fill in this part) 3. Full name, address and postcode of the or of Supreme Plastics Holdings Limited each applicant (underline all surnames) Supreme House 300 Regents Park Road Finchley London N3 2TL 8180622001 Patents ADP number (if you know it) If the applicant is a corporate body, give the United Kingdom country/state of its incorporation 4. Title of the invention APPLICATION OF ZIPPERS TO FILM MATERIAL 5. Name of your agent (if you have one) W P Thompson & Co "Address for service" in the United Kingdom Eastcheap House, Central Approach to which all correspondence should be sent Letchworth Garden City (including the postcode) Hertfordshire SG6 3DS Patents ADP number (if you know it) 158003 6. If you are declaring priority from one or more Priority application number Date of filing Country earlier patent applications, give the country (if you know it) (Day/month/year) and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number If this application is divided or otherwise 7. Number of earlier application Date of filing derived from an earlier UK application, (Day/month/year) give the number and the filing date of the earlier application 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))

The

**Patent** 

Patents Form 1/77

26JAN04 E867898-1 D00335.

P01/7700 0.00-0401500/47#CCCUNT CHA

Patents Form 1/77

# Pents Form 1/77

).	Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document	
	Continuation sheets of this form	0
	Description	5
	Claims	2
	Abstract	1 //
	Drawing(s)	3-1-3 /
10.	If you are also filing any of the following, state how many against each item.	
	Priority documents	
	Translations of priority documents	
	Statement of inventorship and right to grant of a patent (Patents Form 7/77)	
	Request for preliminary examination and search (Patents Form 9/77)	1
	Request for substantive examination—— (Patents Form 10/77)	
	Any other documents (Please specify)	
11.		We request the grant of a patent on the basis of this application
		Signature  Date
		W P Phompson & Co 23 January 2004
12.	Name and daytime telephone number of person to contact in the United Kingdom	Dr Robert Ackroyd 01462 682139

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505
- b) Write your answers in capital letters using black ink or you may type them.
- (i) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

# APPLICATION OF ZIPPERS TO FILM MATERIAL

This invention relates to methods of and apparatus for 5 applying reclosable fastener profiles, otherwise known as zippers, to film material, where the zipper is applied transversely to the direction of movement of the film material.

Transverse web or cross-web technology is now well known, 10 where a zipper is applied transversely to the longitudinal axis of a film, but by its very nature the inclusion of means to stop the film and apply the zipper makes a continuously operating unit inefficient.

It is therefore an object of the present invention to 15 provide a method of and apparatus for applying the zipper while the film material or web is still moving at the normal line rate, thus maintaining the efficiency of the line operation.

Our co-pending international patent application 20 PCT/GB2003/002158 describes and claims such an apparatus and method. The object of the present application is to provide further such apparatus and method.

According to the present invention there is provided an apparatus for applying a zipper strip to a film transversely to the direction of movement of the film, comprising means for producing continuous movement of the film in the said direction, applicator means arranged to receive the zipper strip, to present it to the film at a first location and to move with the film in the said direction to a second location, and sealing means arranged to move together with the applicator means in the said direction from the first to the second location to effect sealing of the zipper strip to the film during the said movement from the first to the second location, the applicator means and the sealing means being arranged for reciprocal return movement in a direction

opposite to the said direction from the second location to the first location.

Preferably, the application means and the sealing means are located at respective opposite sides of the film.

5 The sealing means conveniently comprises a heated sealing bar.

The applicator means and the sealing means may be reciprocally driven by a linear motor.

Conveniently, the applicator means is movable towards and 10 away from the film in a direction substantially perpendicular to the said direction.

The invention also provides a method of applying a zipper strip to a film transversely to the direction of movement of the film, the method comprising moving the film continuously.

15 in said direction, presenting a zipper strip to the film at a first location by an applicator means, applying sealing means to the film at the first location, moving the applicator means and the sealing means together with each other in the said direction from the first to the second location to effect sealing of the zipper strip to the film during the movement from the first to the second location, and returning the applicator means and sealing means in a direction opposite to the said direction from the second to the first location.

An embodiment of the invention will now be described by 25 way of example with reference to the drawings of this specification, in which:

Figure 1 is a somewhat schematic perspective view of an apparatus for applying zipper strips transversely to a moving web;

Figure 2 is a somewhat schematic perspective view of a horizontally-operating form-fill-seal packaging machine incorporating the apparatus of figure 1; and

Figure 3 is a schematic side view showing the operation of the apparatus of figure 1.

Figure 1 shows a web of plastics film 10 which is moving

continuously in the direction A shown by an arrow. A guideway 12 for a linear motor 14 is mounted beneath the film 10. The linear motor can be driven to move linearly in first and second, opposite directions B,B' shown by arrows.

A support platform 16 is mounted on the motor 14 and carries centrally a pneumatic cylinder 18, to which compressed air can be supplied by suitable pressure and control means (not shown). To each side of the cylinder 18, the platform carries a guide 20a, 20b, each of which consists of a piston-10 and-cylinder arrangement. Similarly, electrical control means control the motor 14.

The cylinder 18 and guides 20a, 20b carry at their upper ends a zipper applicator bar 22. The applicator bar 22 is movable below the film 10 in first and second, opposite - 15 directions C,C' shown by arrows, the directions being perpendicular to the direction A of movement of the film 10. The applicator bar 22 has a longitudinal groove 24 which is shaped and dimensioned to receive lengths of zipper 26. The zipper 26 passes through the nip of counter-rotating drive 20 rollers 28a, 28b which feed the zipper 26 into the groove 24. A reciprocating blade 30 cuts the zipper into sections of predetermined length, usually less than the width of the film 10. The zipper 26 consists of continuous lengths of interengaging releasable male and female fastener strips, for 25 example of any of many known types.

A heated sealing bar 32 is positioned above the film 10 and is fixed relative to the platform 16. The sealing bar 32 is shaped along its lower edge 34 to align with the upper edge of the applicator bar 22 adjacent to the groove 24 in the 30 applicator bar and thereby to apply heat to the film 10 at a location adjacent the location of a length of zipper 26 located in the groove 24 of the applicator bar 22 and presented to the film 10 by upward movement of the applicator bar 22.

Figure 2 of the drawings shows the general arrangement

of a horizontally-operating form-fill-seal packaging machine which includes the apparatus of figure 1 which is indicated by the reference numeral 50. The apparatus 50 is orientated with the applicator bar 22 uppermost in figure 2: any 5 orientation is possible. In the orientation of figure 2, a suitable vacuum device (not shown) is included to retain zipper lengths in the groove 24.

The film 10 is stored in a roll 52 which can rotate to allow the film to be drawn by a pair of feed rollers 54a, 54b 10 through the apparatus 50, whence it passes around further guide rollers 56a, 56b before being fed to a forming box 58 of a conventional horizontal form-fill-seal packaging machine. Articles 60 to be packaged are fed in the direction E shown by an arrow on a conveyor belt (not shown) to the forming box -15 58, where, in the conventional manner, the film 10 is folded around the article 60 and the longitudinal edges of the film 10 are brought together and sealed to each other to form Subsequently to this, and at a location a back seal. downstream of the forming box 58, the folded film passes 20 between a pair of heated cross-seal jaws 62a, 62b which form transverse seals between the inner faces of the folded film and also sever the film to provide individual sealed packages 64 containing the articles 60.

It should be mentioned that, in accordance with cross-web 25 technology, the zipper 26 is cut into lengths which are slightly less than one-half of the width of the film 10, the male and female profiles of the zipper lengths being engaged with each other. The lengths of zipper are located by the applicator bar 22 centrally of the film 12. Thus, when the 30 film is folded in the forming box 58, the portions of the film to each side of the zipper length form the sides and one face of the eventual package. The length of zipper is attached to what becomes the other face of the package, so that, by the operation of the cross-seal jaws, heat is applied to the first 35 face of the package to seal the zipper strip to that face and,

after that, the film is severed into individual packages. The packages thus have a transverse heat seal at each end and, positioned inwardly of one of the seals, an openable and reclosable seal formed by the zipper strips for use after 5 opening of the package by breaking the adjacent heat seal.

Figure 3 of the drawings shows the operation of apparatus of figure 1. In figure 3, the film 10 is shown moving in the direction A. The applicator bar 22 is shown movable between its first and second limit positions 22', 22", determined by 10 the linear motor 12. The lengths of zipper 26 are presented to the applicator bar 22 when it is in its first limit position 22'. The bar is then raised by the pneumatic cylinder 18 in the direction C until it contacts the lower surface of the film 12. Further movement in the direction C \* 15 results in movement of the film 10 against the sealing bar to apply sealing heat to the opposite face of the film 12, the lower edge of the sealing bar coming to rest on the upper (as shown in figure 1) edge of the applicator bar 22 adjacent the groove 24.

20 The applicator bar 22 and seal bar 32 are then moved in the direction B by the linear motor, until the second limit position 22" is reached. During this movement, the speed of travel of the motor 14 and of the film 10 are equal to each other. At the second limit position 22", the applicator bar 25 22 is moved away from the film 10 in the direction C', prior to its being returned to the first limit position 22' by movement in the direction B' by the linear motor 14. cycle is then repeated to apply the zipper strips at spaced intervals along the length of the film 10. The motor 14 is 30 capable of producing a very rapid acceleration deceleration of the applicator bar 22 and the sealing bar 34, these taking place during the time taken for the movements in the directions C and C'.

#### CLAIMS:

- 1. An apparatus for applying a zipper strip to a film transversely to the direction of movement of the film, comprising means for producing continuous movement of the film 5 in the said direction, applicator means arranged to receive the zipper strip, to present it to the film at a first location and to move with the film in the said direction to a second location, and sealing means arranged to move together with the applicator means in the said direction from the first to the second location to effect sealing of the zipper strip to the film during the said movement from the first to the second location, the applicator means and the sealing means being arranged for reciprocal return movement in a direction opposite to the said direction from the second location to the 5 first location.
  - 2. An apparatus according to claim 1, in which the applicator means and the sealing means are located at respective opposite sides of the film.

20

- 3. An apparatus according to claim 1 or 2, in which the sealing means comprises a heated sealing bar.
- 4. An apparatus according to any preceding claim, in 25 which the applicator means and the sealing means are reciprocally driven by a linear motor.
- 5. An apparatus according to any preceding claim, in which the applicator means is movable towards and away from the film in a direction substantially perpendicular to the said direction.
- 6. A method of applying a zipper strip to a film transversely to the direction of movement of the film, the 35 method comprising moving the film continuously in said

direction, presenting a zipper strip to the film at a first location by an applicator means, applying sealing means to the film at the first location, moving the applicator means and the sealing means together with each other in the said direction from the first to the second location to effect sealing of the zipper strip to the film during the movement from the first to the second location, and returning the applicator means and sealing means in a direction opposite to the said direction from the second to the first location.

10

- 7. A method according to claim 6, in which the applicator means is moved at the first location in a direction substantially perpendicular to the said direction of movement of the film, in order to apply the zipper to the film and is 15 moved in the opposite direction at the second location prior to its return movement to the first location.
- 8. An apparatus for applying a zipper to a film, substantially as hereinbefore described with reference to the 20 drawings.
  - 9. A method of apparatus for applying a zipper to a film, the method being substantially as hereinbefore described with reference to the drawings.


#### **ABSTRACT**

### APPLICATION OF ZIPPERS TO FILM MATERIAL


An apparatus for application of zippers to film 5 material 10 comprises an applicator bar 22 for presenting precut lengths of zipper 26 to the film and a heated sealing bar 32 for sealing the pre-cut lengths to the film. The applicator bar and sealing bar are mounted for movement with the film on a linear motor 14. A pneumatic cylinder 18 raised 10 the application bar towards the film 10. The application bar moves in direction C to apply the zipper to the film 10 moving in direction A, then moves with the sealing bar and the film in direction B, away from the film in direction C', back to its starting position in direction B', then towards the film 15 again in direction C after being loaded with a further length of zipper.

(Figure 1)

C:\TEMPFI\SPEC2.WPD\RA\sjc



	i de		
		d.	








Fig.3

,